

ECOCLEAN™ HSDI - Rail Fuel Detergent

Description	<p>ECOCLEAN™ HSDI is a chlorine-free multifunctional additive package for use in all types of diesel fuel and gas oil including biofuel blends. By counteracting the problems of injector fouling and filter blocking in modern HSDI diesel engines, ECOCLEAN™ HSDI can improve drivability, recover lost power, increase fuel economy and reduce exhaust emissions.</p>	Typical Properties	<p>Density 15°C 0.91 kg/l Kinematic Viscosity 40°C 4 cSt Kinematic Viscosity 20°C 5 cSt Closed Flash Point (PMCC) 62°C Pour Point -39°C</p>
	<p>ECOCLEAN™ HSDI will help inhibit the formation of black sludge and sediment in diesel fuel and gas oils, which form from thermal preventing fuel filter blocking.</p>	Handling	<p>ECOCLEAN™ HSDI can be added either concentrated or in a stock solution using Fuelcare metering pumps.</p>
	<p>ECOCLEAN™ HSDI will not cause formation of haze in wet fuel systems.</p>	Safety & First Aid	<p>Observe usual precautions for handling concentrated chemicals and blending additives into fuel.</p>
Composition	<p>A solution of polymeric dispersant and functional antifoulant co-additive in high flash aromatic solvent.</p>	Comments	<p>ECOCLEAN™ HSDI is compatible with other commonly used fuel additives and with engine and fuel system materials of construction.</p>
Applications	<p>Road, Marine, Heavy Industrial & Power Generation.</p>	Service Contacts	<p>Product Conforms to EC 1907/2006 (REACH). Please contact Fuelcare technical team: www.fuelcare.com or +44 (0)1743 360784.</p>
Dosage Rate	<p>ECOCLEAN™ HSDI is dosed at a rate of 1000ppm by volume (1 Litre of ECOCLEAN™ HSDI to 1000 Litres of fuel).</p>		

The information contained in this document is provided free of charge and is based on technical data that Fuelcare believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Fuelcare accepts no liability for any loss, damage or expense arising from, or in connection with, the use of the information. Furthermore, none of the contents of this publication should be taken as a license to operate under any patent, nor as a recommendation to infringe any patent.